



ALL-AMERICAN SUPPLY

*High-Tech Materials From The Outer Reaches
Of Space to the Depths of the Ocean*

Solar-Aero Space-Weapons-Nuclear
301 Eubank SE Albuquerque, NM 87123
(505) 299-7655 FX: (505)292-2495
Website: www.allamericansupply.com
Email: insulate@allamericansupply.com



EMERALD RAM® HS PLASTIC

EMERALD RAM® HS Plastic is a premium alumina-chrome product which is phospho-bonded. Its unsurpassed resistance to acid and neutral as well as basic slags allows it to survive the most severe corrosive/erosive environments.

TEMPERATURE CLASSIFICATION: 800-3400°F

MATERIAL REQUIRED PER CUBIC FOOT: 200 LBS.

PYROMETRIC CONE EQUIVALENT: 40

PHYSICAL PROPERTIES:

Test Temp (°F)	Bulk Density(pcf)	Modulus of Rupture (psi)	Permanent Linear Change (%)	Thermal Conductivity (Btu in./hr.sqft/°F)
230	191	1360	--	--
500	--	--	--	20.0
1000	--	--	-0.2	17.5
1500	--	--	--	15.8
2000	--	--	--	14.2
2550	--	3820	-0.3	--
2910	--	3490	-0.5	--

CHEMICAL ANALYSIS – CALCINED BASIS (Wt %):

Al ₂ O ₃	SiO ₂	P ₂ O ₅	Cr ₂ O ₃	Other
87.1	1.5	3.2	7.6	0.6

Manufactured by Vesuvius USA.